



[®]
**Krono
Original**
High Quality
Made by Kronospan

2023
flooring
assortment

O.R.C.A.[®]
MOISTURE DEFENSE TECHNOLOGY

www.krono-original.com

Welcome to our world!

PRODUCT OVERVIEW	04
SURFACE TEXTURES	06
FEATURES GUIDE	07
O.R.C.A. TECHNOLOGY	08

rganic FLEX	14
rganic LONG	24
rganic CLASSIC 12	30
rganic CLASSIC 8	38
rganic CLEVER LONG	52
rganic CLEVER SILENT	58
rganic CLEVER	66

FORMAT OVERVIEW	74
ACCESSORIES	76
DECOR OVERVIEW	82
PACKAGING INFORMATION	83



Product overview

	Collection Name	Durability (Wear Resistance)	Coreboard (Water Protection)	Thickness	Utilization Class	Pet- proof	Residential Guarantee ^{*3}	Bevel	Joint	Synchro	SKUs
O.R.C.A. Flooring	Organic^{*1} FLEX 638 x 322 mm 25.12" x 12.68" 1288 x 189 mm 50.71" x 7.44"	Titanium Ultra	^{*2} O.R.C.A. MOISTURE DEFENSE TECHNOLOGY	7 mm PerfectPad [®] Cork	34		30 years	V4	1 clic 2go pure+	-	11
	Organic^{*1} LONG 2003 x 195 mm 78.86" x 7.68"	AC5	^{*2} O.R.C.A. MOISTURE DEFENSE TECHNOLOGY	8 mm	33		30 years	V4	1 clic 2go pure+	Yes	6
	Organic^{*1} CLASSIC 12 1288 x 195 mm 50.71" x 7.68"	AC5	^{*2} O.R.C.A. MOISTURE DEFENSE TECHNOLOGY	12 mm	33		30 years	V4	1 clic 2go pure+	Yes	8
	Organic^{*1} CLASSIC 8 635 x 327 mm 25.00" x 12.87" 1285 x 192 mm 50.59" x 7.56"	AC5	^{*2} O.R.C.A. MOISTURE DEFENSE TECHNOLOGY	8 mm	33		30 years	V4	1 clic 2go pure	Yes^{*4}	17
	Organic^{*1} CLEVER LONG 2003 x 245 mm 78.86" x 9.65"	AC5	^{*2} O.R.C.A. MOISTURE DEFENSE TECHNOLOGY	6 mm	32		20 years	V4	1 clic 2go pure+	-	6
	Organic^{*1} CLEVER SILENT 1288 x 195 mm 50.71" x 7.68"	AC5	^{*2} O.R.C.A. MOISTURE DEFENSE TECHNOLOGY	6+1 mm PS Pad	32		20 years	V4	1 clic 2go pure+	-	9
	Organic^{*1} CLEVER 1288 x 195 mm 50.71" x 7.68"	AC5	^{*2} O.R.C.A. MOISTURE DEFENSE TECHNOLOGY	6 mm	32		20 years	V4	1 clic 2go pure+	-	8

Σ 65

*1 Consists of natural wood and an organic chemical binder.

*2 24 h surface water protection as stipulated by NALFA (North American Laminate Floor Association) with additional 100 h+ surface water protection according to works standard specification KRONOSPAN WN-101, www.100hour-test.com, up to 100 h no leakage


*3 According to warranty terms

*4 Selected decors

The floor that takes it all

Surface textures

The look and feel of real wood and stone




Features guide

Your benefits at a glance



Residential guarantee

All floors are put through a series of rigorous tests in order to comply with international quality standards, which is why we grant an extensive residential warranty with every product.



Real groove

Bevelled edges on all four sides of the plank ensure an authentic floorboard look.



Anti bacterial comfort

A.B.C. Anti Bacterial Comfort inhibits the growth of bacteria on your flooring and provides you with the peace of mind that comes from a healthy home environment. (Tested germs: Staphylococcus aureus).



Authentic embossed

The synchronous pores follow the grain of the decor, meaning they flawlessly mimic the character of natural wood.



Microscratch protect

The robust surface protects your flooring against micro-scratches that can be caused by strong mechanical stresses or the claws of house pets.




Pet-proof

Thanks to the robust surface, which is also undaunted by small mishaps, the flooring is exceptionally well-suited for life with house-pets.



Light-resistant

The flooring is light-resistant: Even on days when the sun is shining for hours, your flooring remains non-fading according to rating 6, the highest level of the Blue Wool Scale.



Silent

Due to an integrated pad, the flooring reduces impact sound, echoes and vibrations. An additional underlay is not required, which saves time and money.



Robust

This flooring is amazingly robust due to its super durable surface. Moving furniture or falling objects are not a problem because of its high pressure and impact resistance.



Warm underfoot

Due to its flexible design layer, the flooring has comfortable haptics and is warm underfoot.



Anti-slip class

Safety is something we put great emphasis on. Classification in anti-slip classes has been achieved through specially developed surface structures, which address the requirements for floor coverings in the workplace and commercial areas where a high risk of slipping is present.



Anti-slip class

Classification:
R9 and R10 according to DIN 51330,
A: according to DIN 51097



Soft touch

The flooring has a soft surface and feels very comfortable.




Anti-static

The flooring provides complete protection against unpleasant shocks. The Anti-static is built-in and guaranteed for the life of the floor.

How O.R.C.A. technology works

Each fiber is encapsulated with a special binder that prevents it from absorbing water



Short fiber length and geometry reduces potential expansion

Micro expansion on the edges seals the connection between planks



Wood's self sealing property

Wood expands when exposed to moisture and in doing so seals itself, preventing liquid penetration

Boat builders take advantage of wood's natural self sealing property

Wine barrels are still sealed using this time tested method





MOISTURE DEFENSE TECHNOLOGY

The floor that combines the best

O.R.C.A. = Organic Rigid Coreboard Abrasion-proof**

O.R.C.A. is twice as good

It unites the best qualities of biologically based floors and conventional waterproof floor coverings. In O.R.C.A., organic** materials are made resistant to liquids by means of a special technology.

O.R.C.A. makes the flooring usable anywhere

The innovative O.R.C.A. board makes it possible to install the flooring even in private bathrooms*** where, until now, only vinyl or tiles could be used. Furthermore, thanks to their outstanding thermal stability and non-fading properties, O.R.C.A. products also can be used in conservatories and rooms with floor-to-ceiling windows.

O.R.C.A. floors are extremely robust

The robust surface with an AC5 durability rating, protects the flooring against microscratches that can be caused by strong mechanical stresses such as moving furniture, falling objects or the claws of house pets. Thanks to its durable properties, which are also undaunted by small mishaps, O.R.C.A. floors are exceptionally well-suited for life with house pets.

O.R.C.A. is built better because it is more elaborately manufactured

The wood fibers are mechanically processed multiple times in a special production process to obtain especially small fibers. Further on in the manufacturing process a specially developed, organic-chemical binding agent surrounds even the finest fibers and isolates them from moisture.

The floor that's not afraid of water

100 h+ splash-water protection guaranteed*


Little accidents occur almost daily. Wherever such things are bound to happen, it's worth relying on O.R.C.A. Kitchen, dining room, bathroom – O.R.C.A. is a perfect fit.



Scan the QR code and convince yourself!



* 24 h surface water protection as stipulated by NALFA (North American Laminate Floor Association) with additional 100 h+ surface water protection according to works standard specification KRONOSPAN WN-101, www.100hour-test.com, up to 100 h no leakage
** Consists of natural wood and an organic chemical binder
*** Please observe installation instructions



O.R.C.A.[®]

MOISTURE DEFENSE TECHNOLOGY

The flooring that is naturally nature-friendly



www.blauer-engel.de/uz176



Sustainable

Sustainability isn't just a buzzword for us, but part of our corporate strategy. It would never cross our minds to use wood that didn't come from sustainably managed forests.

CO₂-negative

O.R.C.A. boards are CO₂-negative because manufacturing O.R.C.A. releases less CO₂ than was stored by the tree.

Organic

Our O.R.C.A. board consists of components based on biological raw materials and organic-chemical binding agents (synthetic resins) and thus is organic.

PVC-free

Our O.R.C.A. products contain no PVC*.

* May contain traces of PVC, e.g. from packaging




Organic FLEX 

with **PerfectPad®** Cork 1 mm



The feel-good floor

1.80 m
70.87"



Format

Wood design 1288 (50.71") x 189 (7.44") x 7 mm

Tile design 638 (25.12") x 322 (12.68") x 7 mm

- ✔ Feels, looks and sounds like vinyl
- ✔ Up to 90 % natural wood
- ✔ Avoids approx. 98 % of plastic
- ✔ Warm underfoot
- ✔ Soft surface, comfortable haptics
- ✔ Silent due to Cork Pad
- ✔ Robust surface
- ✔ Thermally stable (-15 to 60 °C room temperature)



EN 16511



K503 Pebble Manor Oak, TN

Organic FLEX 

with **PerfectPad®** Cork 1 mm



K506 Lunar Range Oak, TN

Thickness 7 mm
Lock 1clic 2go pure+



EN 16511



K500 Pearl River Oak, TN



K503 Pebble Manor Oak, TN



K506 Lunar Range Oak, TN

Organic FLEX 

with PerfectPad® Cork 1 mm



K501 Sand River Oak, TN

Thickness 7 mm
Lock 1clic 2go pure+



EN 16511



K501 Sand River Oak, TN



K504 Tuscan Manor Oak, TN



Organic FLEX 

with **PerfectPad®** Cork 1 mm



K502 Flax River Oak, TN

Thickness 7 mm
Lock 1clic 2go pure+




EN 16511



K502 Flax River Oak, TN



K507 Hazel Range Oak, TN



K505 Tobacco Manor Oak, TN

Organic FLEX 

with **PerfectPad®** Cork 1 mm



K510 Brooklyn Dark, US

Thickness 7 mm
Lock 1clic 2go pure+



EN 16511



K508 Brooklyn Mist, US



K509 Brooklyn Vibe, US




K510 Brooklyn Dark, US



Durable like you







K284 Summer Breeze Oak, RO

1.80 m
70.87"



Format

2003 (78.86") x 195 (7.68") x 8 mm

-  Elegant long plank format
-  Installation in bigger dimensions
-  Laying through doors
-  Authentic wood texture
-  Integrated anti-static effect
-  Thermally stable (-15 to 90 °C room temperature)



EN 13329



K451 Silverdale Oak, HO



K451 Silverdale Oak, HO

Thickness 8 mm
Lock 1clic 2go pure+



EN 13329



K451 Silverdale Oak, HO



K284 Summer Breeze Oak, RO



K450 Firebrand Oak, HO

Organic LONG 



8156 Red River Hickory, VH

Thickness 8 mm
Lock 1clic 2go pure+



EN 13329



K327 Hillside Oak, RO



K287 Steelworks Oak, HO




8156 Red River Hickory, VH

Organic CLASSIC 12 



Relax, it's O.R.C.A.

1.80 m
70.87"



Format

1288 (50.71") x 195 (7.68") x 12 mm

- ✔ 12 mm strong planks
- ✔ Authentic wood texture
- ✔ Integrated anti-static effect
- ✔ Thermally stable (-15 to 90 °C room temperature)



EN 13329



K453 Biscotti Oak, HO

Organic CLASSIC 12 



K063 Organic Oak, TO

Thickness 12 mm
Lock 1cllic 2go pure+



EN 13329



K063 Organic Oak, TO



K453 Biscotti Oak, HO



K326 Sundance Oak, RO

Organic CLASSIC 12 



K477 Natural Carpenter Oak, CM

Thickness 12 mm
Lock 1cllic 2go pure+



EN 13329



K413 Blackwater Oak, OE




K392 Atomic Oak, RO



K477 Natural Carpenter Oak, CM

Organic CLASSIC 12 



K412 Doubloon Oak, OE

Thickness 12 mm
Lock 1clic 2go pure+



EN 13329



K412 Doubloon Oak, OE



K489 Bourbon Hills Oak, HO




Organic CLASSIC 8 



Makes the kitchen
a living room





1.80 m
70.87"



Format

Wood design 1285 (50.59") x 192 (7.56") x 8 mm

Tile design 635 (25.00") x 327 (12.87") x 8 mm

-  The multi-talent floor for the whole family
-  Beautiful wood- and tile decors in different textures
-  Integrated anti-static effect
-  Thermally stable (-15 to 90 °C room temperature)



EN 13329




1536 Michigan Oak, NL

Organic CLASSIC 8 



1532 Atlantic Oak, TO

Thickness 8 mm
Lock 1cllic 2go pure



EN 13329



1514 Arctic Oak, LP



1532 Atlantic Oak, TO




1521 Caribbean Light Oak, NL

Organic CLASSIC 8 



1533 Ontario Oak, TO

Thickness 8 mm
Lock 1cllic 2go pure



EN 13329



1536 Michigan Oak, NL



1533 Ontario Oak, TO




1517 Pacific Oak, PO

Organic CLASSIC 8 



1579 Hudson Oak, LP

Thickness 8 mm
Lock 1cllic 2go pure



EN 13329



1531 Baltic Oak, NL




1579 Hudson Oak, LP

Organic CLASSIC 8 



1530 Bristol Oak, RF

Thickness 8 mm
Lock 1clic 2go pure



EN 13329



1523 Montreal Oak, NL



1530 Bristol Oak, RF




1519 Victoria Oak, HO

Organic CLASSIC 8 



1539 Liverpool Oak, HC

Thickness 8 mm
Lock 1clic 2go pure



EN 13329



1538 Toronto Oak, NL



1539 Liverpool Oak, HC

Organic CLASSIC 8 



1527 Amazon Slate, OS



1527 Amazon Slate, OS

Thickness 8 mm
Lock 1cllic 2go pure



EN 13329



1525 Mississippi Slate, RT



1528 Submarine Slate, AS




1526 Yukon Slate, OS

Organic CLEVER LONG 



Goes a long way

1.80 m
70.87"



Format

2003 (78.86") x 245 (9.65") x 6 mm

- ✔ Slim Fit
- ✔ Traditional long plank format
- ✔ Installation in bigger dimensions
- ✔ Laying through doors
- ✔ Thermally stable (-15 to 90°C room temperature)



EN 13329




K406 Eurus Oak, NL

Organic CLEVER LONG 



K445 Ethereal Oak, NL

Thickness 6 mm
Lock 1cllic 2go pure+



EN 13329



K406 Eurur Oak, NL



K419 Armoury Oak, NL




K445 Ethereal Oak, NL

Organic CLEVER LONG 



K462 Gold Volcano Oak, NL

Thickness 6 mm
Lock 1cllic 2go pure+



EN 13329



K444 Spindrift Oak, NL



K462 Gold Volcano Oak, NL



K482 Twilight Sterling Oak, NL




Organic CLEVER SILENT 

with PS 1 mm





Silence is creativity

1.80 m
70.87"



Format

1288 (50.71") x 195 (7.68") x 6+1 mm

-  Silent due to integrated silent pad
-  Additional underlay is not required, which saves time and money
-  Easy installation
-  Thermally stable (-15 to 90 °C room temperature)



EN 13329



K482 Twilight Sterling Oak, NL


Organic CLEVER SILENT 

with PS 1 mm



5966 Khaki Oak, NL

Thickness 6+1 mm
Lock 1cllic 2go pure+



EN 13329



5543 Colorado Oak, NL



5966 Khaki Oak, NL



5946 Rockford Oak, NL


Organic CLEVER SILENT 

with PS 1 mm



K461 Antique Volcano Oak, NL

Thickness 6+1 mm
Lock 1cllic 2go pure+



EN 13329



K419 Armoury Oak, NL



5985 Sherwood Oak, NL



K461 Antique Volcano Oak, NL


Organic CLEVER SILENT 

with PS 1 mm



8168 Tobacco Oak, NL

Thickness 6+1 mm
Lock 1cllic 2go pure+



EN 13329



K482 Twilight Sterling Oak, NL



K468 Gondola Oak, NL




8168 Tobacco Oak, NL



The family's favourite





5966 Khaki Oak, NL

1.80 m
70.87"



Format

1288 (50.71") x 195 (7.68") x 6 mm

-  Slim fit
-  Easy installation
-  Classic format
-  Thermally stable (-15 to 90 °C room temperature)




EN 13329





K418 Longbow Oak, NL

Thickness 6 mm
Lock 1clic 2go pure+



EN 13329



8461 St. Moritz Oak, NL



K406 Eurus Oak, NL




K418 Longbow Oak, NL

Organic CLEVER waterproof



5948 Renaissance Oak, NL

Thickness 6 mm
Lock 1cllic 2go pure+



EN 13329



K470 Natural Cashmere Oak, NL



5948 Renaissance Oak, NL




Organic CLEVER waterproof



K395 Tornado Oak, NL

Thickness 6 mm
Lock 1clic 2go pure+



EN 13329



K462 Gold Volcano Oak, NL



K395 Tornado Oak, NL



K415 Aeolus Oak, NL


Format overview

All thicknesses and formats

Organic FLEX PerfectPad® Cork 1 mm	189 mm 7.44"	1288 mm / 50.71"
Organic FLEX PerfectPad® Cork 1 mm	322 mm 12.68"	638 mm / 25.12"
Organic LONG	195 mm 7.68"	2003 mm / 78.86"
Organic CLASSIC 12	195 mm 7.68"	1288 mm / 50.71"
Organic CLASSIC 8	192 mm 7.56"	1285 mm / 50.59"
Organic CLASSIC 8	327 mm 12.87"	635 mm / 25.00"
Organic CLEVER LONG	245 mm 9.65"	2003 mm / 78.86"
Organic CLEVER SILENT PS 1 mm	195 mm 7.68"	1288 mm / 50.71"
Organic CLEVER	195 mm 7.68"	1288 mm / 50.71"

PerfectPad®

Available on all O.R.C.A. products



K501 Sand River Oak, TN

Accessories that match your floor perfectly

Selected range of products

Every floor needs proper accessories. We can supply you with the ideal equipment for all types of flooring. One contact, one supplier – which makes everything so much simpler for you.

Underlays

Depending on the situation in the room, attention must be paid to the correct underlay material when installing the flooring. For this we offer multiple solutions.

Skirting boards

Choose from a range of skirtings in various decors that match all KronoOriginal® floors. Our advanced fixing system makes it quick and simple to achieve a perfect installation.

Additional accessories

If you still look for the proper skirting board, corner pieces, aluminium adhesive tape for sealing or you are done and wish to mop the floor, take a look at the following pages and discover the wide range of accessories.

Get more out of your O.R.C.A. products

With suitable accessories, you leave nothing to chance –









whether you are looking for the right underlay, skirting boards, end pieces, corners and profiles for a harmonious finish, practical tools or the right cleaning agent.











Discover the full range!








Accessories

Article	Illustration	Item No. [Customer Code]	Description	Packing Unit
Underlay PUR 1.0		98535 [EX PUR1.0_ORCA]	Material: PET film + polyurethane heavy-duty layer + non-woven material	1 x 10 m = 10 m ²
Underlay PUR 2.0		98571 [EX KO98571N]	Material: Polyurethan and mineral fillers	1 x 7.5 m = 7.5 m ²
Underlay WOOD 5.0		90171 [EX 90171]	Material: Wood fibres	0.79 x 0.59 m x 15 = 7 m ²
PE foil		98111 [EX FOLIE2.0]	Material: Polyethylene	2 x 7.5 m = 15 m ²
Aluminium tape		98191 [EX ALUBAND]	Thickness: 0.048 mm Width: 50 mm	1 roll (50 m)
Transition profile, 2-part, screw-in		91231 91221	900 mm or 2700 mm	1 pcs.
Ramp profile, 2-part, screw-in		91251 91241	900 mm or 2700 mm	1 pcs.
End profile, 2-part, screw-in		91211 91201	900 mm or 2700 mm	1 pcs.








Article	Illustration	Item No. [Customer Code]	Description	Packing Unit
Transition click profile		98391 98381	900 mm or 2700 mm	1 pcs.
Ramp click profile		98411 98401	900 mm or 2700 mm	1 pcs.
End click profile		98371 98361	900 mm or 2700 mm	1 pcs.
3in1 profiles		95315 [EX 95315-A002] anodised stainless steel	1000 mm	10 pcs.
K58C moisture resistant		95316 [EX xxxxSLH-ORCA]	2600 x 58 x 18 mm	10 pcs.
K58C Design skirting board		97345 [EX 97345-9002] (white) 97345 [EX 97345-L056] (silver)	2400 x 58 x 18 mm	10 pcs.
Accessories for K58C skirting board		98011 98001 98021	External corners Internal corners End caps	90° in packs of 2 90° in packs of 2 in packs of 4, 2 left and 2 right
Mounting clips		91501 [EX 50510]	-	Box of 30 pieces, complete with screws and rawl plugs

Accessories

Article	Illustration	Item No. [Customer Code]	Description	Packing Unit
Tapping-block		90274 [EX Schlagholz_ORCA]	300 x 50 x 30 mm	12 pcs.
Spacer		90292 [EX ABSTANDSKEIL]	-	30 spacer per bag
Clickguard™ joint sealant		90431 [EX 94270]	-	125 ml ≈ ca. 10 m²
Wax-repair set, mixable		90511 [EX F996]	-	7 wax blocks, 1 melting tool, 1 cleaning combed scraper, 1 green/white pad, 1 grey abrasive pad
Cleaner for floors with O.R.C.A.		90411 [EX REINIGER_ORCA]	-	750 ml



Decor overview

Flooring Type	Collection Name	Decors
O.R.C.A. flooring	Organic FLEX	 K500 K503 K506 K501 K504 K502 K507 K505 K508 K509 K510
	Organic LONG	 K451 K284 K450 K327 K287 8156
	Organic CLASSIC 12	 K063 K453 K326 K413 K392 K477 K412 K489
	Organic CLASSIC 8	 1514 1532 1521 1536 1533 1517 1531 1579 1523 1530 1519 1538 1539 1527 1525 1528 1526
	Organic CLEVER LONG	 K406 K419 K445 K444 K462 K482
	Organic CLEVER SILENT	 5543 5966 5946 K419 5985 K461 K482 K468 8168
	Organic CLEVER	 8461 K406 K418 K470 5948 K462 K395 K415


■ decor editions

Packaging information

Plank Size	Thickness	Planks/ Pack.	m ² / sq ft Pack.	Weight/Pack. [kg lbs]	Pack./Pallet = m ² sq ft
638 x 322 mm 25.12" x 12.68" 1288 x 189 mm 50.71" x 7.44"	7 mm 7 mm	12 10	2.47 26.53 2.43 26.19	16 35 16 35	32 = 79 849 52 = 126 1356
2003 x 195 mm 78.86" x 7.68"	8 mm	7	2.73 29.42	20 44	40 = 109 1177
1288 x 195 mm 50.71" x 7.68"	12 mm	6	1.51 16.21	16 36	52 = 78 843
635 x 327 mm 25.00" x 12.87" 1285 x 192 mm 50.59" x 7.56"	8 mm 8 mm	11 9	2.28 24.58 2.22 23.89	17 38 16 36	32 = 73 786 52 = 115 1242
2003 x 245 mm 78.86" x 9.65"	6 mm	8	3.93 42.30	23 50	36 = 141 1521
1288 x 195 mm 50.71" x 7.68"	6+1 mm	9	2.26 24.32	13 29	52 = 117 1265
1288 x 195 mm 50.71" x 7.68"	6 mm	11	2.76 29.73	16 35	52 = 144 1546



Made by Kronospan



www.blauer-engel.de/uz176

* Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions). Statement on level of emission of volatile substances in indoor air posing a toxic threat during inhaling – on a scale from A+ (very low-emission) to C (high-emission).

www.eco-institut.de/e/portfolio/emissions-dans-lair-interieur



www.krono-original.com
www.facebook.com/KronoOriginal



www.kronospan.com
info@krono-original.com